

# Ampatex® Ombrello

Weather protection / construction period cover,  
fully self-adhesive



- > Transparent: furring, chalklines, penetrations, etc. remain visible
- > Adhesive made of UV acrylate: moisture does not affect the adhesive
- > Natural weathering period of 3 months: sufficient time for construction phase
- > Easy to install and non-slip: for faster work and safe walking during the construction phase

Technical details		Value	Standard
s <sub>D</sub> value		3,5m	EN 12572
Weight		130 g/m <sup>2</sup> (± 10%)	EN 1849-2
Tear resistance	longitudinal	110N /5cm	EN 12311-2
	transverse	100N /5cm	
Tear elongation	longitudinal	60%	EN 12 311-2
	transverse	80%	
Resistance to further tearing (nail shaft)	longitudinal	80 N	EN 12310-1
	transverse	80 N	
Fire performance		E	EN 13 501-1
Waterproofing at 2 kPa		passed	EN 1928
Width of overlap		≥10 cm	
Straightness		<75 mm/10 m	EN 1848-2
Temperature resistance		-40°C – +80°C	
Remains durable after artificial ageing		passed	EN 1296
Outdoor weathering, pitched roof >10° and wall		3 months	
Outdoor weathering, ceiling		1 month	

**Area of application:** Transparent, full-surface adhesive vapour check and weather protection membrane. Used, for example, to temporarily cover wooden ceilings during the transport, assembly and construction phase or to ensure airtightness on wooden materials and other substrates.



CE  
13984

ISO 9001  
Swiss Research

\*Conditions for the twenty-year premium warranty include registering the building object and the Ampack products used. In addition, our products must be used as part of a system. For further details, please see our General Warranty Conditions.

## Delivery forms

Item no.	Identification	Roll dimensions	Pallet contents
7640442091384	Ampatex® Ombrello	1,5 m × 50 m = 75 m <sup>2</sup> Liner division: 25 cm / 125 cm	28 rolls = 2100 m <sup>2</sup>



- 3 Ampatex® Ombrello**  
Weather protection/  
construction period  
cover, fully self-  
adhesive



## Tips when laying

Before applying the tape, any pointed or sharp edges and objects such as stones, wood splinters, etc. must be removed. Ensure that the substrate is clean, dry and free of dust, ice and grease. Tip: Install on the construction site with two or three persons. In windy conditions, work with the wind direction. Align **Ampatex® Ombrello** with the markings, imprint or chalkline. Overlap **Ampatex® Ombrello** by at least 10 cm. Note the dashed overlap line for this.

Roll out the membrane so far that it can be aligned. It is best to peel off the narrow cover strip first and thereby fix the mem-

brane in the desired position over the entire length. Then peel off the wide cover strip. While peeling off, rub the membrane well on the surface with a soft broom or similar. **Important: Ensure adequate drainage when applying on horizontal or flat components.**

Protect the membrane from mechanical damage. Ensure cleanliness on the construction site. Cover exposed areas such as walkways if necessary. **Ampatex® Ombrello** is a temporary weather protection solution and is not intended for flat-roof waterproofing. When severe weather with above-average precipitation or hurri-

cane-like wind loads is forecast, it must be additionally secured, e.g. with PVC tarpaulins.

For panel joints and connections, use **Ampacoll® Flexx pro** 150 mm. Penetrations are best sealed with **Ampacoll® BK 535** (50, 80 or 120 mm). Substrates may have to be pre-treated with **Ampacoll® Primax** or **Ampacoll® Airmax**.



Please observe the recommendations for use and further system products in our adhesives matrix



Further information and detailed documentation at [www.ampack.biz](http://www.ampack.biz)

Sales via specialist dealers

Ampack Switzerland: +41 71 858 38 00  
Ampack Austria: +43 5523 53433  
Ampack Germany: +49 7621 1610264  
Ampack France: +33 4 50 83 70 54  
Ampack Italy: +39 471 053 475  
Ampack Ireland: +353 91 394 467  
**www.ampack.biz**



The following information may have been superseded by new findings or developments. Current Information can be found at [www.ampack.biz](http://www.ampack.biz). © Ampack AG, Rorschach, 10.2022

4133EU/EXX.YYFO(AR)1022