

Ampacoll® Airmax

Spray primer



- > Sprayable; faster than with a brush
- > Short drying time
- > Permanently tacky
- > Makes overhead and vertical work easier
- > Can also be used indoors

external
internal

Technical details	Value
Base	Synthetic rubber
System	Contains solvent
Drying time on a dry background	+20°C approx. 10 min. +5°C approx. 20 min. +0°C approx. 30 min. -5°C approx. 40 min.
Shelf life / storage	Unopened at +5°C to +25°C (frost free) Best before: see bottom of can. Keep out of direct sunlight.
Coverage	30–70 running metres on 60 mm width, depending on surface
Application temperature	Surroundings and surface: -5°C to +35°C
Resistance to temperature	-20°C to +80°C



 **ISO 9001**
Swiss Research

Area of application: Spray primer and primer for adhesives for Ampacoll® adhesive strips on porous surfaces, such as masonry, plaster, concrete, bare wood, soft wood fibre board, etc. Suitable for use in difficult conditions (cold, damp).

Delivery forms				
Item no.	Identification	Dimensions	Box contents	Pallet contents
7640115536273	Ampacoll® Airmax, spray primer	0,5 l	12 cans	70 boxes



Ampacoll® Primax
Solvent-free
paint-on primer

Application tips

Surfaces / materials to be bonded

Ampacoll® Airmax spray primer is a primer for Ampacoll® adhesive strips on porous or rough surfaces, such as masonry, plaster, concrete, bare wood, soft wood fibre board, etc.

Preparation

Surfaces, connections and materials to be bonded must be clean and dry and free of dust and grease. Remove any concrete or cement residue.

Application

Protect plastics and sensitive surfaces by covering them before spraying. Evenly apply a strip of primer which is as wide as the adhesive tape to the surface. Spray absorbent surfaces slowly and intensively (in a single process). Protect sprayed surfaces from dust and moisture, etc.

Allow the primer to dry. Depending on the temperature and surface, this usually takes between 10 and 40 minutes. In the case of humidity or low temperatures the curing

time may increase. The primer remains tacky. The primer is completely dry when fingerprints can no longer be seen or are barely visible.

Perform overhead applications first with a fresh can. The spray head can be turned twice. By turning the small black nozzle it is possible to direct the spray jet. By turning the whole spray head to the positions Low, Medium, High it is possible to regulate the spray volume.

Cleaning

Splashes must be removed immediately. If work is interrupted, clean the spray head with a cloth. Regularly clean the spray head with a cloth to prevent blockages. To do so, spray a tiny amount of primer onto a cloth and then wipe this over the spray head.

Note

Ampacoll® Airmax spray primer is not compatible with paint. Paints, varnishes and plastics may dissolve. Test whether the primer is compatible with adjacent materials.

Safety instructions

Please also read the safety data sheet.



Please observe the recommendations for use and further system products in our adhesives matrix



Further information and detailed documentation at www.ampack.biz

Sales via specialist dealers

Ampack Switzerland: +41 71 858 38 00
Ampack Austria: +43 5523 53433
Ampack Germany: +49 7621 1610264
Ampack France: +33 4 50 83 70 54
Ampack Italy: +39 471 053 475
Ampack Ireland: +353 91 394 467
www.ampack.biz



The following information may have been superseded by new findings or developments. Current Information can be found at www.ampack.biz. © Ampack AG, Rorschach, 07.2022

5575EU/ENXX..YY(AR)0722